



PAKAWASTE
WASTE HANDLING SYSTEMS



92479



All PAKAWASTE Equipment conforms to the EC machine safety directive (2006/42/EC previously 98/37/EC & amendments)

PORTABLE COMPACTORS



PORTAKRUSH 500

The PORTAKRUSH 500 achieves exceptional compaction ratios utilising a high performance pivot action blade which keeps the charge box area free from debris. These efficient machines are market leaders with large numbers currently in use. They achieve a compaction ratio of between 4 and 6:1 on a wide selection of waste materials.

PAY LOAD	: Up to 5.5 tonnes (dependant on materials)
CYCLE TIME	: 50 seconds
MOTOR RATING	: Single - 5.5 kw
FREE AIR SPACE	: 10.7 cu.m (14 cu.yds)

TECHNICAL SPECIFICATION

SINGLE CYLINDER

Overall length	3780 mm (148.75 in)
Overall height	2210 mm (87 in)
Loading height	950 mm (37.375 in)
Loading aperture height	705 mm (27.75 in)
Loading aperture width	1210 mm (47.625 in)
Ram depth	1035 mm (40.75 in)
Volume	10.1 cu.m (13.2 cu.yd)
CHEM volume per stroke	1.4 cu.m (1.8 cu.yd)
Cylinder thrust	18.7 tonnes (18.4 tons)*
Normal operating pressure	148 kg/sq.cm (2100 psi)*
Dry cycle time	50 secs
Motor rating	5.5 kw (7.5 hp)
Power supply rating (415v 3 phase)	16 amp
Power supply rating (240v single phase & neutral)	16 amp
Oil reservoir capacity	50 ltr (11.1 gals)
Total weight	2.5 tonnes (2.46 tons)

* **Projected design capabilities**

PAKAWASTE LIMITED

For further information and technical data, contact our sales staff at:

Rough Hey Road - Preston PR2 5AR . TEL +44 (0)1772 796688 . FAX +44 (0)1772 792474
EMAIL sales@pakawaste.co.uk . technical@pakawaste.co.uk . WEB www.pakawaste.co.uk

Pakawaste Ltd. reserves the right to make alterations to equipment design and specifications without prior notice.

Photographs for illustration purposes only.