



# PAKAWASTE

WASTE HANDLING SYSTEMS

For further information and technical data, contact our sales staff at:  
Rough Hey Road, Preston, PR2 5AR  
t: +44 (0)1772 796688 f: +44 (0)1772 792474  
e: sales@pakawaste.co.uk w: www.pakawaste.co.uk

Pakawaste Ltd. reserves the right to make alterations to equipment design and specifications without prior notice.

Photographs for illustration purposes only.

All PAKAWASTE equipment conforms to the EC machine safety directive (2006/42/EC previously 98/37/EC & amendments)

PORTABLE

STATIC

SPECIALIST

## POWERKRUSH 95

The Powerkrush 95A is the largest static compactor in our range. The huge charge area is most suitable not only for large, bulky items, but also for heavy, industrial waste that requires extra pressure for volume reduction. Typical applications include civic amenity sites and transfer stations where massive volumes of waste product can be compacted tidily and speed of disposal is essential. Heavy duty hoppers can be designed to suit individual loading applications. It is used in conjunction with a 40 cubic yard container.

### TECHNICAL SPECIFICATION

### SINGLE CYLINDER

Overall length (to container face)	4450mm
Overall width (to compactor body)	1972mm
Height (top of charge box)	1300mm
Charge box top opening length	2000mm
Charge box top opening width	1524mm
Charge box depth	908mm
Charge box volume	2.4m <sup>3</sup>
CHEM volume per stroke	2.5m <sup>3</sup>
Operating compaction force (normal) @ 2100psi	27 tonnes
Boost force (pinning) @ 2400psi	30.8 tonnes
Ram face pressure (normal)	2.4kg/cm <sup>2</sup>
Motor rating	15kW (20hp)
Power supply rating (415V 3 phase)	63amp 3PH+E, C or D rated
Total weight	3.5 tonnes

\* Projected design capabilities

If this machine is situated outside of the earth equi-potential zone it must be protected by a triple pole RCD with a 30 milliamp tripping facility (NOT A SOCKET)

