



**PAKAWASTE**  
WASTE HANDLING SYSTEMS



92479



All PAKAWASTE Equipment conforms to the EC machine safety directive (2006/42/EC previously 98/37/EC & amendments)

## SPECIALIST COMPACTORS



## STATIC ROTOKRUSH

The **Rotokrush** compaction system is a unique product which provides the customer with the flexibility to load up to 50 cubic yard containers with bulky materials such as packing cases, pallets, wood, glass fibre and other industrial / difficult medium density waste materials whilst achieving compaction ratios on average of 4:1.

The **Static Rotokrush** is fixed to a firm concrete base with single containers being placed in front of the machine for continuous compaction. Compacting into open containers allows fast, easy loading by forklift truck or loading shovel making this an ideal machine for high throughput sites.

## TECHNICAL SPECIFICATION

Required headroom	6800 mm (267.75 in)
Roller travel limit	6600 mm (259.78 in)
Overall space required container length	1200 mm (72.75 in)
Maximum container width	2630 mm (103.5 in)
Distance between forklift pockets	1150 mm (44.5 in)
Roller width	1700 mm (67 in)
Roller diameter	1150 mm (45.25 in)
Roller weight	1.2 tonnes (1.18 tons)
Total weight	3.26 tonnes (3.21 tons)
Motor size	7.5 kw (10 hp)
Power supply	16 amp
Minimum level of waste	500 mm (19.75 in)

**PAKAWASTE** LIMITED

For further information and technical data, contact our sales staff at:

Rough Hey Road - Preston PR2 5AR . TEL +44 (0)1772 796688 . FAX +44 (0)1772 792474  
EMAIL sales@pakawaste.co.uk . technical@pakawaste.co.uk . WEB www.pakawaste.co.uk

Pakawaste Ltd. reserves the right to make alterations to equipment design and specifications without prior notice.

Photographs for illustration purposes only.